



Terranota Ltd. P.O. Box 1703 Invercargill 1703  
 Telephone: 0800 003 006  
 Fax: 03 215 8248  
 Email: [enquiries@boundaryline.co.nz](mailto:enquiries@boundaryline.co.nz)  
 Website: [www.boundaryline.co.nz](http://www.boundaryline.co.nz)

Model  
**SentryPanel® Rod-Top  
 1800mm**

Important Note: SentryPanel panel specifications do not meet the requirements of the Pool & Safety fence regulations. Contact [technical@boundaryline.co.nz](mailto:technical@boundaryline.co.nz) for alternative solutions if required.

Rail Profile	40x40mm Square Aluminium with R3 radius on corners
Picket Profile	25x25mm Square Aluminium with R3 radius on corners
Panel Length	2250x1800mm
Flanged Post	65x65x1900mm (125mm square flange) M12 Fixings
In-ground Post	65x65x2500mm
Post Caps	External Aluminium Caps (Standard) or Internal Plastic Caps (Optional)

Bracket Fixing	External Aluminium Bracket (adjustable brackets available for angled corners)
Pedestrian Gate Hardware	Unsprung hinge, with Key-Lockable Latch
Custom Gate Hardware	Contact <a href="mailto:technical@boundaryline.co.nz">technical@boundaryline.co.nz</a> for further options
Driveway Swing Gate	See Driveway Gate Specification Sheet
Driveway Sliding Gate	See Sliding Gate Specification Sheet

Issue Date	18-5-2016
Scale	1:20
Revision	-.-

**Unless Otherwise Specified:**  
 All units in Millimetres  
 Linear Tolerances +/- 0.5mm overall  
 Angular Tolerances +/- 0.5mm overall