EXTERNAL POWDERCOATED ALUMINIUM
POST CAP (Standard - shown) OR
INTERNAL PLACTIC CAPS (Optional)

POWDERCOATED
STEEL BRACKET

DETAIL A
1:2.5

FIXED TO BACK OF POST
USING 1 x 12gx25mm
GALVANISED PAINTED
SELF-DRILLING SCREW

2260

48

45

1220

A

50x50 FLANGED POST

CONCRETE 17.5mpa MIN

SLOPE TOP OF CONCRETE
TO ALLOW WATER TO
DRAIN AWAY FROM POST

'GOOD GROUND' 100kpa
ALLOWABLE BEARING AS
DEFINED BY NZS: 3604

Boundaryline

Terranota Ltd. P.O. Box 1703 Invercargill 1703
Telephone: 0800 003 006
Fax: 03 215 8248
Email: enquiries@boundaryline.co.nz
Website: www.boundaryline.co.nz

© Copyright June 2017. All rights reserved to Terranota Ltd.

SIZE	DATE ISSUED	REV.	
A4	2020-06-15		DO NOT SCALE DRAWING

SCALE 1:32	SHEET 1 of 1	WEIGHT	UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS

Model

GreenScreen 1200mm

Rail Profile	N/A
Panel Profile	50x50mm Wire Aperture, Powdercoated Black
Panel Dimensions	2233mm x 1220mm
Flanged Post	50x50x1300mm (125mm Square flange) M12 fixings
In-ground Post	50x50x1800mm

Bracket Fixing	External Steel Bracket
Post Caps	External Aluminium Caps (Standard) or Internal Plastic Caps (Optional)
Standard Gate Hardware	N/A
Child Safety Gate Hardware	N/A