



 Boundaryline

PICKETPANEL

Install Guide

Guide to installing Boundaryline's PicketPanel Fencing

This guide will serve as your resource for installing PicketPanel. If you have any questions, please contact our Technical Team on 0800 003 006 or email technical@boundaryline.co.nz.

Before you start

Describe your site details when ordering materials.

Identify your soil type/ground conditions, this will determine the required concrete and footing details.

Check with local council regulations on boundary fencing and confirm the locations of underground services before commencing digging.

For your reference

A DAR5025-BK bracket can be utilised to install panels in a curved line, see [page 09](#)

PicketPanel fence panels are pre-assembled and all designed with raking functionality for easy installation.

The brackets are designed to rake from 0 to 15 degrees, the rails can be modified to allow for further raking. It should be kept in mind that raking will decrease the gaps between pickets, and they may require respacing.


Included in this guide are the steps on how to modify the rail for increased raking and how to respace the pickets, see [pages 10](#) and [11](#).

Glossary

A complete panel consists of:




Posts 50x50 or 65x65mm
In-ground or Flanged




Fence Panel
Pickets are all fixed at 100mm centres



Brackets x 4 (6 x brackets for 1800mm panels)
Fixed to the post using 2 x 12gx30mm tek screws



Tek Screws
Attaches the brackets to the panels and posts



Post Caps
Designed to slot into the posts

Installation Overview

STEP 1. Laying Out The Fence Line.....04

Lay out the fence line using the post size and panel lengths to calculate the post centre.

STEP 2. Dig Post Holes.....05

Mark and dig out post holes. Ensure the centre of hole remains in line with the post centres.

TIP: Use spray paint to mark a line in front of the hole to maintain the post centres.

STEP 3a. Installing Posts - In-Ground Posts.....06

Ensure there is approximately 50-100mm of ground clearance.

Pour the concrete around the post and brace as required to keep the post level and true.

STEP 3b. Installing Posts - Flanged Posts.....07

Ensure the surface is flat, firm and level.

Fix the posts in position using fixing appropriate to the surface type.

STEP 4a. Installing Panels.....08

STEP 4b. Installing The Panels in a Curved Line.....08

Ensure the posts are set. Slot the rails onto the brackets, don't fix the panel onto the bracket until after attaching the brackets to the post.

Position and fix one side of the panel to the post and then lower the other side down and fix into place.

Once the brackets are fixed to the post, fasten the rail to the bracket to fix the panel in place.

STEP 4c. Installing Panels Raking Over 15 Degrees.....09

EXTRA. Respacing Pickets.....10

Tools Required	Optional Tools	Safety Gear
☐ Tape Measure	☐ Powered Auger - 200mm diameter	☐ Safety Boots
☐ Spade/Shovel	☐ Hacksaw/Powered metal cutting saw	☐ Gloves
☐ Level	☐ Laser-level	☐ Helmet
☐ String Line	☐ Rivet Gun	☐ Eye Protection
☐ Concrete		☐ Hearing Protection
☐ Drill		☐ Sun Protection

Ensure you have the right tools before installing PicketPanel


STEP 1 | Laying Out The Fence Line

- a. Accurately establish the property boundary. Determine and mark any legal boundaries and/or underground services. *If the boundary pegs can't be found, request a copy of the site plans from the council, or get a surveyor to correctly establish the boundary.*
- b. Lay out a string line to establish the placement of the fence. A string line will ensure the fence line remains straight.
- c. To determine the measurements for the post positions, see table A:
- d. Mark the post positions with post markers or spray paint. Measurements should start from the centre of the first post and continue to be measured from each post centre to the next.
- e. Once all post positions and post centers are determined and marked, use the string line or laser level to make sure all straight lines are aligned.

Table A						
Panel length	+	Clearance*	+	Post size	=	Post centre
2430mm	+	12mm	+	50mm	=	2492mm
2430mm	+	12mm	+	65mm	=	2507mm

**Clearance between the post and panel allows space for the bracket*

Where to measure the panel and posts



When installing PicketPanel, it is recommended to give consideration to the spacings of the posts, to avoid the need to respace the pickets when installing.

The panels are 2430mm wide, with the centre of each picket spaced at 100mm apart. If posts require being closer together than the standard panel length, keeping the posts distances in multiples of 100mm, where possible, (i.e., 2330mm, 2230mm etc), will result in simply trimming off the excess of the panel and prevent the need for respacing pickets.

If this is not achievable, a guide to respacing pickets is on [page 10](#)

STEP 2 | Dig Post Holes

If using **Flanged Posts**, go to **page 07**.

If using **In-Ground Posts**, dig the holes for the posts using hand tools and/or a powered auger.

The diameter of all post holes are required to be at least 200mm in diameter.

Table B - Required post hole dimensions


Post Size	Suggested Hole Diameter
50x50	200-300mm
65x65	300mm

When digging the holes, ensure the post holes don't taper inwards towards the bottom, they need to be either vertically straight and parallel, or be wider at the bottom than the opening.

Table C - Post lengths required will increase accordingly to cater for these ground conditions

Soil Type	Minimum hole depth	Approximate concrete required per post hole
Firm Earth	600mm	2 bags - 20kg bag
Loose Fill	900mm	3 bags - 20kg bag




For post hole dimensions, see tables **B** and **C**, which provide guidance depending on post size and soil type.



STEP 3a | Installing Posts - In-Ground Posts

Posts should be installed in 'good ground' as defined by NZS3604

- Place the post into the hole and ensure the height and position are correct using a tape measure and/or a laser level.
- Ensure there is sufficient height on the post, from ground level to the top of the post, to allow for the panel height and ground clearance. Ground clearance is measured from the bottom of the pickets. A minimum of 50mm is recommended.
- Pour the concrete around the post, taking care to keep the post at the right height and position. Regularly check with a spirit level to ensure the post is plumb and ensure the post remains square to the fence line and does not turn as the concrete is laid around it.
- If the fence line follows any contours in the land or the fence line is curved, regularly check the height of the posts while working down the fence line to ensure a good visual line along the top of the fence.
- Allow for the concrete to completely set before installing the panels.



TIP For standard 50x50 or 65x65mm aluminium posts, a fairly dry concrete mix can be used which will hold the post in place without any bracing while the concrete dries. However, the site must be revisited before the concrete sets firm to recheck post alignment. Any heavier posts, i.e. gate posts, should be concreted in place and braced until the concrete is dry.



STEP 3b | Installing Posts - Flanged Posts

- a. Ensure the surface is firm, level and clean.

Concrete surfaces are required to be 20MPa minimum and be at least 120mm thick. The bolts require at least 90mm of embedment into the concrete and must be 40mm away from any edges.

Wooden Surfaces* are required to have 120mm embedment into the joist, with extra allowance for the decking timber. Thicker decking timber will require longer screws to maintain the 120mm embedment depth requirement.

- b. Check post position, alignments and measurements for the panels are correct before bolting down the posts.
- c. Fix the posts in place with four fixings ensuring the correct screws are used for the material surface. *Details for timber and concrete options below.*




Fixings - indicative



In concrete:

4x M12 Ramset Anka screws or similar with minimum 90mm embedment



Fixings - indicative



In timber:



4x 12mm coach screws with minimum 120mm embedment

*When installed on timber surfaces, PicketPanel **does not** comply with F4 (Fall From Height) requirements. For **all** installations requiring F4 compliance, refer to the PicketPanel PS1 for details.

STEP 4a | Installing Panels

Once the posts are completely set and secured, the panels can be installed.



- a. On the posts, measure to confirm the placement of the brackets, allowing for 50-100mm of clearance between the ground and the bottom of the pickets. The panels should sit flush with the top of the posts. *For ground clearance, 50mm minimum is recommended.*
- b. Slot the brackets onto the rails, then place the panel between the posts into its correct position and attach the brackets to the post. Since PicketPanel can rake, once one side is attached, the other side can be easily lowered into position.
- c. Once the brackets are attached, the rail can be fastened to the bracket to lock the panel into its final position.



STEP 4b | Installing Panels in a Curved Line

If PicketPanel is being installed in a curved line

- a. Using a DAR5025-BK bracket measure 100mm from the top of the post to the top of the bracket. Secure the brackets onto the post with the provided Tek Screws.
- b. Position the panel at the required angle (if the angle is more than what the bracket allows, you may need to trim the rail down see **page 09** on how to trim the rails).
- c. Attach the panel to the bracket using Tek Screws through the top and bottom of the bracket.




STEP 4c | Installing Panels Raking Over 15 Degrees


If PicketPanel is being installed with a raking angle exceeding 15 degrees.

Please note: When raking panels, the spacing between the pickets will *decrease*. Raking more than 20 degrees may require you to respace the pickets. A guide on resacing pickets is available on [page 10](#).


- a. Measure the angle that the panel will rake to and cut that from the rail. The cutouts will be the opposite at either end of the rail. Also measure a 7mm cutout from the long edge of the rail, this will keep the end of the rail from protruding.
- b. Slot the brackets onto the rails, then place the panel between the posts into its correct position, ensuring the bracket on the lower end is inverted to accommodate the rake. Attach the brackets to the posts using the provided Tek Screws.
- c. Fasten the rail to the bracket to fix the panel in its final position.




Example of cut angles of rail for extra raking



Tek Screw is driven through the top of the rail after attaching the bracket to the post



Final fixed position



EXTRA | Respacing Pickets

Tools required

- ☐ Drill with 5mm drill bit
- ☐ Rivets (4.8mm aluminium with grip range of 3.2 to 4.8mm)
- ☐ Rivet Gun or Hand Riveter
- ☐ Tape Measure

Step 1:

Remove the slip cover from the back of the rails on the panel.
The cover is designed to slide out of the channel. *Fig. 1*

Step 2:

Drill out the rivets with a 5mm drill bit. *Fig. 2*

Be careful not to allow the chuck of battery drill to rub on the rail, this can damage the powdercoated finish.

Step 3:

Space out pickets evenly.

Small 5-10mm differences are typically not noticeable.

TIP Use a spacer to keep the picket gap widths consistent

Step 4:

Drill new hole, through both the rail and the back side of the picket, be sure to avoid drilling right through to the front side of the pickets. *Fig. 3*

TIP Mark the drill bit with a piece of tape at 5mm of depth to make sure you don't overdrill

Step 5:

Rivet the new pickets on using a hand riveting tool or a rivet gun. *Fig. 4*

Step 6:

Replace the slip cover.

The previous rivet hole should be covered over with the refixed pickets.

Figure 1




Figure 2




Figure 3





Figure 4



Auckland

43 Noel Burnside Road
09 250 1144

Christchurch

19 Mania Road
03 347 3191

Invercargill

60 Basstian Street
03 211 5145

0800 003 006

enquiries@boundaryline.co.nz
boundaryline.co.nz

Please note: This document is only intended to be a general guide, as every property & situation is different.

Any installation work, including the use of power equipment is completely the responsibility of the person(s) installing.

All persons using power equipment must be trained & certified to use the equipment & must wear all applicable personal protection gear.

Terranota Ltd cannot accept any responsibility for any faulty installation or damage or injury arising from installation work.